



## PIC-IPD48D55

48MP/10FPS, Lowlight, ePTZ



| Sensor & Lens            |   |
|--------------------------|---|
| Type                     | CMOS, 4x12MP, 1/1.7"  |
| Min illumination         | Color: 0.01 Lux B/W: 0 Lux with IR  |
| Day & Night              | IR Cut Filter with Auto Switch  |
| WDR                      | DWDR  |
| DNR                      | 2D, 3D  |
| Electronic shutter       | 1s to 1/50,000s   |
| Lens                     | Fixed 5.5mm   |
| Viewing angle (H)        | 180°  |
| Pan/Tilt                 |   |
| Pan range/Speed          | ePTZ  |
| Tilt range/Speed         | ePTZ  |
| Options                  | Preset, Patrol  |
| Encoding standard        |   |
| Video compression        | H.264, MJPEG  |
| Video Bit rate           | 800Kbps-48Mbps, CBR/VBR   |
| No. Streams              | 3 - 4x(4000x3000), 1920x1080, 720x576   |
| Audio compression        | N/A   |
| Image Index              |   |
| Max Image size           | 48MP 4x(4000x3000)  |
| VCA                      | N/A   |
| Frame Rate               | 10fps@48MP 4x(4000x3000)  |
| Image setup              | Brightness, Saturation, Contrast, ROI, Flip Mode, HLC, BLC, Defog, Privacy Mask, Picture Overlay              |
| Network function         |   |
| Intelligent Alarm        | Motion Detection, IP Conflict, ARP protection, Mask Alarm, Tampering Alarm, Alarm in/Out, user authentication |
| Protocols                | IPV4, IPV6, IGMP, , HTTP, FTP, SMTP, , DNS, DDNS, RTP, RTSP, TCP, RTCP, UDP, DHCP, PPPoE, QoS                 |
| Interface protocol       | ONVIF (Profile S), API, SDK, CGI  |
| General function         | Reset Button  |
| Function Interface       |   |
| Network port             | 1x RJ45 10M / 100M /1000M   |
| Local storage            | N/A   |
| Video port               | N/A   |
| Audio (in/out)           | N/A   |
| Serial interface         | RS-485  |
| Alarm interface (in/out) | 1/1   |
| General Specification    |   |
| MTBF                     | 50,000 hours  |
| Approval                 | CE, FCC, UL   |
| Protection               | Optional, Hardware  |
| IR type                  | N/A   |
| IR distance              | N/A   |
| Operation conditions     | -40°C~60°C, 0~95% RH  |
| Power supply             | DC 12 V ± 10%,  |
| Power consumption        | Max. 16W  |
| Protection rate          | IP66, IK10  |
| Mounting                 | Surface mount   |
| Dimensions (mm)          | 228x228x330   |
| Weight (Kg)              | 4 KG (Camera Only)  |

### مشخصات مهم

- دوربین دام پانوراما ۴۸ مگاپیکسل
- لوایت
- نمای ۱۸۰ درجه
- بزرگنمایی دیجیتال
- روز / شب
- کاهش نویز دو بعدی و سه بعدی
- دارای سه استریم مستقل
- مقاوم در برابر شرایط محیطی و ضربه
- مصرف انرژی پائین