



PIC-IPD96D55

96MP/10FPS, Lowlight, ePTZ



Sensor & Lens	
Type	CMOS, 8x12MP, 1/1.7"
Min illumination	Color: 0.01 Lux B/W: 0 Lux with IR
Day & Night	IR Cut Filter with Auto Switch
WDR	DWDR
DNR	2D, 3D
Electronic shutter	1s to 1/50,000s
Lens	Fixed 5.5mm
Viewing angle (H)	360°
Pan/Tilt	
Pan range/Speed	ePTZ
Tilt range/Speed	ePTZ
Options	Preset, Patrol
Encoding standard	
Video compression	H.264, MJPEG
Video Bit rate	800Kbps-48Mbps, CBR/VBR
No. Streams	3 – 8x(4000x3000), 1920x1080, 720x576
Audio compression	N/A
Image Index	
Max Image size	96MP 8x(4000x3000)
VCA	N/A
Frame Rate	10fps@96MP 8x(4000x3000)
Image setup	Brightness, Saturation, Contrast, ROI, Flip Mode, HLC, BLC, Defog, Privacy Mask, Picture Overlay
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, ARP protection, Mask Alarm, Tampering Alarm, Alarm in/Out, user authentication
Protocols	IPV4, IPV6, IGMP, , HTTP, FTP, SMTP, , DNS, DDNS, RTP, RTSP, TCP, RTCP, UDP, DHCP, PPPoE, QoS
Interface protocol	ONVIF (Profile S), API, SDK, CGI
General function	Reset Button
Function Interface	
Network port	1x RJ45 10M / 100M /1000M
Local storage	N/A
Video port	N/A
Audio (in/out)	N/A
Serial interface	RS-485
Alarm interface (in/out)	1/1
General Specification	
MTBF	50,000 hours
Approval	CE, FCC, UL
Protection	Optional, Hardware
IR type	N/A
IR distance	N/A
Operation conditions	-40°C~60°C, 0~95% RH
Power supply	DC 12 V ± 10%,
Power consumption	Max. 16W
Protection rate	IP66, IK10
Mounting	Surface mount
Dimensions (mm)	228x228x330
Weight (Kg)	5 KG (Camera Only)

مشخصات مهم

- دوربین دام پانوراما ۹۶ مگاپیکسل
- لولایت
- نمای ۳۶۰ درجه
- بزرگنمایی دیجیتال
- روز / شب
- کاهش نویز دو بعدی و سه بعدی
- دارای سه استریم مستقل
- مقاوم در برابر شرایط محیطی و ضربه
- مصرف انرژی پائین