



PIC-VBM02MDA06

2MP/30FPS, Lowlight, motorized lens, Autofocus



Sensor & Lens	
Type	CMOS, 2MP, 1/2.8"
Min illumination	Color: 0.02 Lux B/W: 0 Lux with IR
Day& Night	IR Cut Filter with Auto Switch
WDR	DWDR
DNR	2D, 3D
Electronic shutter	1s to 1/100,000s
Lens	Motorized 3 - 6mm, 2x Auto Iris
Speed Pan-Tilt	15°/s-5°s
Viewing angle (H)	90.9°- 51.5°
Encoding standard	
Video compression	H.265+, H.265, H.264, MJPEG
Video Bit rate	128Kbps-16Mbps, CBR/VBR
No. Streams	3 - 1920x1080, 1920x1080, 720x576
Audio compression	G.711/G.711U
Image Index	
Max Image size	1920x1080
VCA	Tripwire, Perimeter, Face detection, People counting
Frame Rate	30fps @ 2MP (1920x1080)
Image setup	Brightness, Saturation, Contrast, ROI, Flip Mode, HLC, BLC, Defog, Privacy Mask, Picture Overlay
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, ARP protection, Mask Alarm, user authentication
Protocols	L2TP, IPV4, IGMP, ICMP, ARP, HTTP, 802.1x, FTP, SMTP, UPnP, SIP, DNS, DDNS, NTP, RTP, RTSP, TCP, RTCP, SNMP, UDP, DHCP, PPPoE, QoS
Interface protocol	ONVIF (Profile S, G, T), API, SDK
General function	N/A
Function Interface	
Network port	1x RJ45 10M / 100M
Local storage	MicroSD Card Slot, up to 256GB
Video port	N/A
Audio (in/out)	1/1 Two-way Audio
Serial interface	N/A
Alarm interface (in/out)	2/1
General Specification	
MTBF	50,000 hours
Approval	CE, FCC, UL
IR type	Smart Array IR LEDs
IR distance	100m
Operation conditions	-35°C~60°C, 0~95% RHG
Power supply	DC 12 V ± 25%, POE (IEEE 802.3af)
Power consumption	Max. 17.23W IR OFF
Protection rate	IP66
Mounting	Wall mount
Dimensions (mm)	357x106x194
Weight (Kg)	1.16 KG (Camera Only)

مشخصات مهم

- دوربین بولت متحرک ۲ مگاپیکسل
- لولایت
- لنز موتوری با تنظیم اتوماتیک
- روز / شب
- محدوده داینامیکی 120db
- کاهش نویز دو بعدی و سه بعدی
- آنالیز هوشمند تصاویر
- مجهز به نوردهنده مادون قرمز
- دارای سه استریم مستقل
- پشتیبانی از کارت حافظه داخلی
- مقاوم در برابر شرایط محیطی