



PIC-VX02SA

2MP/50FPS, Super starlight



| Sensor | |
|--------------------------|--|
| Type | CMOS, 2mp 1/1.8" |
| Min illumination | Color: 0.0005 Lux, B/W: 0.0001 Lux |
| Day& Night | IR Cut Filter with Auto Switch |
| WDR | 120 db |
| DNR | 2D, 3D DNR |
| Electronic shutter | 1s to 1/100,000s |
| Lens mount | CS |
| Encoding standard | |
| Video compression | H.265+, H.265, H.264, MJPEG |
| Video Bit rate | 128Kbps-8Mbps |
| No. Streams | 3 – 1920x1080, 1920x1080, 720x576 |
| Audio compression | G.711 |
| Image Index | |
| Max Image size | 1920x1080 |
| VCA | Tripwire, Perimeter, Face detection, People counting |
| Frame Rate | 50 fps @ 2MP (1920x1080) |
| Image setup | Brightness, Saturation, Contrast, Flip Mode, HLC, Defog, Privacy Mask, Picture Overlay |
| Network function | |
| Intelligent Alarm | Motion Detection, IP Conflict, MAC Conflict, Mask Alarm |
| Protocols | IPv4, TCP, ICP, ARP, UDP, PPPoE, RTP, HTTP, HTTPS, FTP, SMTP, UPnP, SNMP, DHCP, DNS, DDNS, NTP, FTP, RTSP, RTCP, QoS |
| Interface protocol | ONVIF (Profile S), P2P, SDK, CGI |
| General function | Reset Button |
| Function Interface | |
| Network port | 2x RJ45 10M / 100M/ 1000M (2x IP Address) |
| Local storage | Micro SD, up to 256GB |
| Video port | YES |
| Audio (in/out) | 1/1 |
| Serial interface | Yes, RS485 |
| Alarm interface (in/out) | 2/1 |
| General Specification | |
| MTBF | 50,000 hours |
| Approval | CE, FCC, UL |
| Protection | TVS 6000V, Lightning/Surge 2000V |
| Operation conditions | -20°C~60°C, 0~95% RHG |
| Power supply | DC 12 V ± 25%, AC 24 V ± 25%, POE (IEEE 802.3af) |
| Power consumption | Max. 6.8W |
| Dimensions (mm) | 151.5x71x65 |
| Weight (Kg) | 0.4 KG (Camera Only) |

مشخصات مهم

- دوربین باکس ۲ مگاپیکسل
- ۵۰ عکس در ثانیه
- سوپر استارلایت
- روز / شب
- محدوده داینامیکی 120db
- کاهش نویز دو بعدی و سه بعدی
- آنالیز هوشمند تصاویر
- دارای سه استریم مستقل
- پشتیبانی از کارت حافظه داخلی
- حفاظت در برابر صاعقه | ولتاژ لحظه ای