



PIC-YBF02S04

2MP/30FPS, Super starlight



Sensor	
Type	CMOS, 2mp 1/2.8"
Min illumination	Color: 0.0008 Lux B/W: 0.0001Lux ; 0 Lux with IR
Day& Night	IR Cut Filter with Auto Switch
WDR	100 db
DNR	3D DNR
Electronic shutter	1s to 1/100,000s
Lens	Fixed 4 mm
Viewing angle (H)	68°
Encoding standard	
Video compression	H.265+, H.265, H.264, MJPEG
Video Bit rate	128Kbps-8Mbps
No. Streams	2 – 1920x1080, 704x480
Audio compression	N/A
Image Index	
Max Image size	1920x1080
VCA	N/A
Frame Rate	25fps @ 2MP (1920x1080)
Image setup	Brightness, Saturation, Contrast, Flip Mode, HLC, Defog, Privacy Mask, Picture Overlay
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, MAC Conflict, Mask Alarm
Protocols	TCP, UDP, HTTP, DHCP, DNS, NTP, RTSP
Interface protocol	ONVIF (Profile S), P2P, SDK, CGI
General function	N/A
Function Interface	
Network port	1x RJ45 10M / 100M
Local storage	N/A
Video port	N/A
Audio (in/out)	N/A
Serial interface	N/A
Alarm interface (in/out)	N/A
General Specification	
MTBF	50,000 hours
Approval	CE, FCC, UL
IR type	2x Array IR LEDs
IR distance	50m
Operation conditions	-35°C~60°C, 0~95% RHG
Power supply	DC 12 V ± 25%, POE
Power consumption	Max. 7.5W IR OFF
Protection rate	IP67
Mounting	Wall mount
Dimensions (mm)	208x82x81
Weight (Kg)	0.5 KG (Camera Only)

مشخصات مهم

- دوربین بولت ۲ مگاپیکسل
- سوپر استارلایت
- لنز ثابت ۴ میلیمتری
- روز / شب
- محدوده داینامیکی 100db
- کاهش نویز سه بعدی
- مجهز به نوردهنده مادون قرمز
- دارای دو استریم مستقل
- مقاوم در برابر شرایط محیطی