



PIR-V0801

NVR 8 CH, up to 10 TB, VCA, ANR



Recording	
Input channels	8
Max recording Res.	8MP
Playback Res. @ FPS	1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8x 720@30
Recording mode	Schedule, Permanent, Event, Motion, Alarm, VCA
Supported cameras	PAVAN, Axis, Bosch, Dallmeier, Dahua, Exom, Hikvision, inMotion, Nazer, Tiandy, UNV & all ONVIF cameras
Decoding	
Video compression	H265+, H.265, H.264
Input bandwidth (Mbps)	40
Output bandwidth(Mbps)	40
Live Res. @ FPS	1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8x 720@30
Display splits	3, 4, 5, 7, 9,
Smart function	
Password policy	3 level
VCA	N/A
Smart Backfill	Yes (ANR)
Mobil monitoring	Yes (Android, iOS)
Alarm management	Anti-disassembly alarm, Network disconnected, Disk offline, Disk abnormal, Illegal access, Running out of space, Space used up, Array damaged, Array degraded, Recording/ Snapshot abnormal, Motion Detection, IP Conflict, MAC Conflict, Mask Alarm
Interfaces	
Storage option	1x SATA up to 10 TB
Raid control	NA
Video	HDMI1 4K, 1x VGA 1080
Audio In/ Out	1/1
Ethernet	1x RJ45 10M/100M
PoE	N/A
USB	Front: 1x USB 2.0/ Rear 1x USB2.0
Serial (PTZ control)	N/A
Contact In/ Relay out	N/A
Backup	USB, LAN
Network protocol	
Protocols	IPV4, IPV6, TCP, UDP, HTTP, HTTPS, UPnP, DHCP, DDNS, NTP, FTP, Unicast, RTSP, SNMP
Interface protocol	ONVIF (Profile S, G, T) ,P2P,SDK
Search function	
Search mode	Date, time, event
Intelligent search	N/A
Playback	8 CH Synchronous
Back up format	Native format (TS), MP4
Log book	Yes via system, warning Alarm, user, operation
General Specification	
MTBF	50,000 hour
Approval	CE, FCC, UL
Operation conditions	-10 °C ~ +55 °C, 10 % ~ 90 %
Power supply	12 VDC
Power consumption	5W (Without HDD)
Mounting	1unit, Desktop
Dimensions (mm)	260x240.2x43.6
Weight (Kg)	1KG

مشخصات مهم

- رکورد 8 کاناله
- ضبط انواع دوربین ها تا 8 مگاپیکسل
- پشتیبانی از فشرده سازی H. 265+
- آنالیز هوشمند تصاویر
- پشتیبانی از کارت حافظه دوربین
- انتقال تصویر روی موبایل
- مدیریت هشدارها
- مصرف انرژی حداقل
- نصب رومیزی