



PIR-V6408R

NVR 32 CH, up to 80TB, VCA, ANR, Raid control



Recording	
Input channels	64
Max recording Res.	12MP
Playback Res. @ FPS	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30
Recording mode	Schedule, Permanent, Event, Motion, Alarm, VCA
Supported cameras	PAVAN, Axis, Bosch, Dallmeier, Dahua, Exom, Hikvision, inMotion, Nazer, Tiandy, UNV & all ONVIF cameras
Decoding	
Video compression	H265+, H.265, H.264
Input bandwidth (Mbps)	320
Output bandwidth(Mbps)	320
Live Res. @ FPS	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30, 32x 960p@25
Display splits	3, 4, 5, 7, 9, 10, 12, 16, 32
Smart function	
Password policy	3 level
VCA	Intrusion Detection, Cross Line Detection, Audio Detection, People Counting, Defocus Detection, Scene Change Detection, Auto Tracking, Object Left Behind, Object Removed
Smart Backfill	Yes (ANR)
Mobil monitoring	Yes (Android, iOS)
Alarm management	Anti-disassembly alarm, Network disconnected, Disk offline, Disk abnormal, Illegal access, Running out of space, Space used up, Array damaged, Array degraded, Recording/ Snapshot abnormal, Motion Detection, IP Conflict, MAC Conflict, Mask Alarm
Interfaces	
Storage option	8x SATA, Max 10 TB for each and 1 eSATA port
Raid control	RAID 0, 1, 5, 6, 10
Video	HDMI1 1080, HDMI2 4K, 1x VGA 1080
Audio In/ Out	1/1
Ethernet	1x RJ45 10M/100M/1000M
PoE	N/A
USB	Front: 2x USB 2.0/ Rear 1x USB3.0
Serial (PTZ control)	RS-232, RS-485
Contact In/ Relay out	16/4
Backup	USB, LAN
Network protocol	
Protocols	IPV4, IPV6, TCP, UDP, HTTP, HTTPS, UPnP, DHCP, DDNS, NTP, FTP, Unicast, Multicast, RTSP, SNMP
Interface protocol	ONVIF (Profile S, G, T) ,P2P,SDK
Search function	
Search mode	Date, time, event
Intelligent search	Face search, Behavior search
Playback	16 CH Synchronous
Back up format	Native format (TS), MP4
Log book	Yes via system, warning Alarm, user, operation
General Specification	
MTBF	50,000 hour
Approval	CE, FCC, UL
Operation conditions	-10 °C ~ +55 °C, 10 % ~ 90 %
Power supply	100-240 VAC
Power consumption	20W (Without HDD)
Mounting	2unit, Rackmount
Dimensions (mm)	442x531x86
Weight (Kg)	5.2KG

مشخصات مهم

- رکورد ۶۴ کاناله
- ضبط انواع دوربین ها تا ۱۲ مگاپیکسل
- پشتیبانی از فشرده سازی H. 265+
- آنالیز هوشمند تصاویر
- پشتیبانی از قابلیت Raid
- پشتیبانی از کارت حافظه دوربین
- انتقال تصویر روی موبایل
- مدیریت هشدارها
- مصرف انرژی حداقل
- نصب داخل رک