



PSW-D2402P

26 Port, Layer3, PoE Switch



Interface	
Total port	26
RJ45 PoE port	24x 10/100 Mbps
RJ45 Uplink port	2x 10/100/1000 Mbps
SFP Uplink port	N/A
PoE budget	600W
Network performance	
Protocols	SNMP, DTP, PAgP, LACP, UDLD, DHCP, ARP, IGMP, CSMA/CD, VTP, TFTP, NTP, SSH, RTSP, MSTP, STP, BOOTP, VLAN,
Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3af, IEEE802.3at
Transfer rate	10Mbps @half duplex , 20Mbps@full duplex, 10BASE-T: 15Kbps/port 100Mbps@half duplex, 200Mbps@full duplex,100BASE-TX: 158Kbps/port 1000Mbps@half duplex, 2000Mbps@full duplex, 1000BASE-TX: 1.5Mbps/port
PoE cable length	10/100Base-TX: Cat5e or above (100m) 1000Base-TX: Cat6 or higher UTP(120m)
Internal bandwidth	8.8 Gb
MAC Address table	16Kb
Console	Web & RS232, Telnet
Transfer pattern	Store & Forward
Manageable	Yes
Port management	Yes
General Specification	
Developed for	IT, Security, VoIP
MTBF	100,000 hrs. MIL-HDBK-217F (25°)
Approval	EN55016
Surge protections	Hardware Optional
Fan	No, natural cooling
Operation conditions	-20°C~60°C, 10~90% RH
Power supply	90~220 VAC
Redundant PSU	N/A
Power consumption	Max. 600W with full PoE use
Protection rate	IP51
LED panel	Power, PoE Activity, Data Activity
Case material	Metal
Mounting	Rackmount
Dimensions (mm)	433x237x45
Weight (Kg)	4.8Kg

مشخصات مهم

- سوئیچ ۲۴ پورت با قابلیت PoE
- لایه ۲ (قابل مدیریت)
- پورت های مگا بیتی
- آپ لینک گیگا بیتی
- ۶۰۰ وات مجموع توان تغذیه
- هماهنگ با پروتکل های سیسکو
- مناسب برای انواع کاربردها
- مدیریت هشدارها
- بدنه فلزی
- نصب داخل رک