



PIC-VBF02IE28

2MP/30FPS, ECO



Sensor & Lens	
Type	CMOS, 2MP, 1/2.7"
Min illumination	Color: 0.01 Lux B/W: 0 Lux with IR
Day & Night	IR Cut Filter with Auto Switch
WDR	120 db
DNR	2D, 3D
Electronic shutter	1s to 1/100,000s
Lens	Fixed 4mm
Viewing angle (H)	91.2°
Encoding standard	
Video compression	H.265+, H.265, H.264, MJPEG
Video Bit rate	128Kbps-16Mbps, CBR/VBR
No. Streams	2 – 1920x1080, 1280x720
Audio compression	G.711A/G.711U
Image Index	
Max Image size	1920x1080
VCA	N/A
Frame Rate	30fps @ 2MP (1920x1080)
Image setup	Brightness, Saturation, Contrast, ROI, HLC, BLC, Privacy Mask
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, ARP protection, Mask Alarm, user authentication, Tampering
Protocols	L2TP, IPV4, IGMP, ICMP, ARP, HTTP, 802.1x, FTP, SMTP, UPnP, SIP, DNS, DDNS, NTP, RTP, RTSP, TCP, RTCP, SNMP, UDP, DHCP, PPPoE, QoS
Interface protocol	ONVIF (Profile S, G, T), API, SDK
General function	Reset button
Function Interface	
Network port	1x RJ45 10M / 100M
Local storage	Micro SD, up to 128G
Video port	N/A
Audio (in/out)	Built in MIC/ N/A
Serial interface	N/A
Alarm interface (in/out)	N/A
General Specification	
MTBF	50,000 hours
Approval	CE, FCC, UL
Protection	TVS 4000V, Lightning/Surge
IR type	Smart Array IR LEDs
IR distance	30m
Operation conditions	-30°C~60°C, 0~95% RHG
Power supply	DC 12 V ± 25%, POE (IEEE 802.3af)
Power consumption	Max. 7W
Protection rate	IP67
Mounting	3-Axis, Wall and surface mount
Dimensions (mm)	167x63x62
Weight (Kg)	0.39 KG (Camera Only)

مشخصات مهم

- دوربین بولت ۲ مگاپیکسل
- لوایت
- سری ارزان قیمت
- لنز ثابت ۴ میلیمتری
- روز / شب
- کاهش نویز دو بعدی و سه بعدی
- نوردهنده مادون قرمز
- دارای سه استریم مستقل
- مقاوم در برابر شرایط محیطی
- مصرف انرژی پائین