



PIC-VDM04135

4MP/30FPS, Light Hunter, motorized lens, Autofocus



Sensor & Lens	
Type	CMOS, 4MP, 1/3"
Min illumination	Color: 0.002 Lux B/W: 0 Lux with IR
Day& Night	IR Cut Filter with Auto Switch
WDR	120 db
DNR	2D, 3D
Electronic shutter	1s to 1/100,000s
Lens	Motorized 2.7-13.5mm, 5x Auto Iris
Viewing angle (H)	101.1° - 28.6°
Encoding standard	
Video compression	H.265+, H.265, H.264, MJPEG
Video Bit rate	128Kbps-16Mbps, CBR/VBR
No. Streams	3 - 2688x1524, 1920x1080, 720x576
Audio compression	G.711A/G.711U
Image Index	
Max Image size	2688x1520
VCA	Tripwire, Perimeter, Face detection, People counting
Frame Rate	30fps@ 4MP (2688x1520), 30fps @ 4MP (2560x1440)
Image setup	Brightness, Saturation, Contrast, ROI, Flip Mode, WB, HLC, BLC, Defog, Privacy Mask, Picture Overlay
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, ARP protection, Mask Alarm, user authentication
Protocols	L2TP, IPV4, IGMP, ICMP, ARP, HTTP, 802.1x, FTP, SMTP, UPnP, SIP, DNS, DDNS, NTP, RTP, RTSP, TCP, RTCP, SNMP, UDP, DHCP, PPPoE, QoS
Interface protocol	ONVIF (Profile S, G, T), API, SDK
General function	Reset Button
Function Interface	
Network port	1x RJ45 10M / 100M
Local storage	MicroSD Card Slot, up to 256GB
Video port	Yes
Audio (in/out)	1/1, Two-way audio
Serial interface	N/A
Alarm interface (in/out)	1/1
General Specification	
MTBF	50,000 hours
Surge Protection	TVS 6000V
Approval	CE, FCC, UL
IR type	Smart IR LEDs
IR distance	40m
Operation conditions	-35°C~60°C, 0~95% RHG
Power supply	DC 12 V ± 25%, POE(IEEE802.3af)
Power consumption	Max. 7.5W
Protection rate	IP67, IK10
Mounting	3-Axis, Wall, Surface mount
Dimensions (mm)	148x148x111.3
Weight (Kg)	0.92 KG (Camera Only)

مشخصات مهم

- دوربین دام ۴ مگاپیکسل
- لایت هانتر
- لنز موتوری ۲/۷-۱۳/۵ میلیمتری
- روز / شب
- محدوده داینامیکی 120db
- کاهش نویز دو بعدی و سه بعدی
- آنالیز هوشمند تصاویر
- نوردهنده مادون قرمز
- دارای سه استریم مستقل
- مقاوم در برابر شرایط محیطی و ضربه
- مقاوم در برابر ولتاژهای سرگردان تا 6KV
- مصرف انرژی پائین