



## PMS-V1000

VMS, 1000 device connections, up to 2000 channels,



Recording	
Number of connected cameras per server	1000 devices or 2000 channels 1000 devices connected via Onvif
Number of connected face recognition terminals	128
Device management	IPC, NVR, face recognition terminal, decoder(standard/expanded), network keyboard, cloud devices, alarm control panel and door access control
Number of 3rd-party alarm control panels /access control devices	30
Numbers of users (online)	1000 (300)
Max Resplution	12MP
Playback Res. @ FPS	4 x 4K@30, 16x 1080p@30, 36x 720p@30, 64xD1
Recording backup	Schedule, Permanent, Event, Motion, Alarm, VCA
Supported cameras	PAVAN, Axis, Bosch, Dallmeier, Dahua, Exom, Hikvision, inMotion, Nazer, Tiandy, UNV & all ONVIF cameras
Decoding	
Video compression	H265+, H.265, H.264
Input bandwidth (Mbps)	512 per server
Output bandwidth(Mbps)	384 per server
Live Res. @ FPS	4 x 4K@30, 16x 1080p@30, 36x 720p@30, 64xD1
Smart function	
Password policy	3 level
VCA	Depend on cameras conditions
Interfaces	
Storage option	Hot-swappable HDDs, 16HDDs (3.5", up to 14TB for each), expandable Max 2 disk enclosures
Raid control	RAID 0, 1, 5, 6, 10, 50, 60
Video	2x HDMI and 1x VGA & Max 2 HDMI4-C and HDMI6-C (optional)
Audio In/ Out	1/1
Ethernet	4x RJ45 10M/100M/1000M, 2x 1000M SFP Ethernet
USB	Rear 4x USB3.0
Serial (PTZ control)	RS-232, RS-485
Contact In/ Relay out	24/8
Backup	USB, LAN
Network protocol	
Protocols	IPV4, IPV6, TCP, UDP, HTTP, HTTPS, UPnP, DHCP, DDNS, NTP, FTP, Unicast, Multicast, RTSP, SNMP
Interface protocol	ONVIF (Profile S, G, C, Q, A, T), P2P, SDK
Search function	
Search mode	Date, time, event
Intelligent search	N/A
Playback	16 CH Synchronous
Back up format	Native format (TS), MP4
Log book	Alarm 200,000, Face capture 3M, Face alarm 3M, Vehicle pass 3M, ACC 3M
General Specification	
MTBF	50,000 hours
Approval	CE, FCC, UL
Operation conditions	-10 °C ~ +55 °C, 10 % ~ 90 %
Power supply	100-240 VAC, Redundant power supply optional
Power consumption	50W (Without HDD)
Mounting	3unit, Rackmount
Dimensions (mm)	482x477x131
Weight (Kg)	10KG

### مشخصات مهم

- سیستم مدیریت تصاویر ۱۰۰۰ کاناله
- مدیریت انواع دوربین ها تا ۱۲ مگاپیکسل
- پشتیبانی از فشرده سازی H. 265+
- پشتیبانی از قابلیت Raid
- پشتیبانی از کارت حافظه دوربین
- انتقال تصویر روی موبایل
- مدیریت هشدارها
- مصرف انرژی حداقل
- نصب داخل رک